

Seat Belt for Forklifts

Forklift Seat Belts - Described in the Regulation guidelines are the utilization of seatbelts and operator restraints on lift trucks. It states that the responsibility falls on the employers' to be able to ensure that each machine, piece of equipment and device is utilized rightly utilized according to the directions of the producer.

Regarding their maintenance, inspection, fabrication, use and design Rough Terrain forklifts ought to meet the guidelines of ANSI Standard ASME B56.6-1992.

Mobile equipment like for example side boom tractors along with a Rollover Protective Structure (ROPS), should include seat belts which meet the Society of Automotive Engineers safety requirements; Society of Automotive Engineers Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whatever mobile machinery includes seat belts required by law, the operator and subsequent passengers have to make sure they use the belts each time the motor vehicle is in motion or engaged in operation in view of the fact that this can cause the machine to become unsteady and therefore, unsafe.

When a seat belt or various operator restraint is needed on a lift truck.

While working a lift truck, the seat belt requirements would depend on several factors. Contributing factors to this determination may include whether or not the the forklift is outfitted with a Rollover Protective Structure, the kind of forklift itself and the year the forklift was made. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

In the case of powered industrial trucks, ANSI Standard ASME B56.1-1993 refers to an operator restraint device, system, or enclosure. An operator restraint device, enclosure or system is intended to assist the operator in lessening the possibility of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The system or restraint device can comprise a seat belt, though a seat belt is not essentially a part of such device or system.